



BS 10 PIPES

N.B. Size	Table	Dia of Flange A	Bore of Slip-on B	Thickness of Flange C	Pitch circle Dia D (PCD)	Dia of Bolt Holes E	No. of Bolts
1/2"	D	95	22.3	4.7	67	14.3	4
	E	95	22.3	6	67	14.3	4
	F	95	22.3	9.5	67	14.3	4
	H	114	22.3	13	83	17.5	4
3/4"	D	102	27.7	4.7	73	14.3	4
	E	102	27.7	6	73	14.3	4
	F	102	27.7	9.5	73	14.3	4
	H	114	27.7	13	83	17.5	4
1	D	114	34.6	5	83	14.3	4
	E	114	34.6	7	83	14.3	4
	F	120	34.6	10	87	17.5	4
	H	120	34.6	14	87	17.5	4
1 1/4"	D	120	43.2	6	87	14.3	4
	E	120	43.2	8	87	14.3	4
	F	133	43.2	13	98	17.5	4
	H	133	43.2	17	98	17.5	4
1 1/2"	D	133	49.5	6	98	14.3	4
	E	133	49.5	9	98	14.3	4
	F	140	49.5	13	105	17.5	4
	H	140	49.5	17	105	17.5	4
2"	D	152	62	8	114	17.5	4
	E	152	62	10	114	17.5	4
	F	165	62	16	127	17.5	4
	H	165	62	19	127	17.5	4
2 1/2"	D	165	75	8	127	17.5	4
	E	165	75	10	127	17.5	4
	F	184	75	16	145	17.5	8
	H	184	75	19	145	17.5	8
3"	D	184	90.5	9.5	145	17.5	4
	E	184	90.5	11	145	17.5	4
	F	203	90.5	16	165	17.5	8
	H	203	90.5	22	165	17.5	8
4"	D	215	116	9.5	178	17.5	4
	E	215	116	13	178	17.5	8
	F	228	116	19	191	17.5	8
	H	228	116	25	191	17.5	8
5"	D	254	144	12.7	210	17.5	8
	E	254	144	14	210	17.5	8
	F	279	144	22	235	22.2	8
	H	279	144	25	235	22.2	8

BS 10 PIPES

N.B. Size	Table	Dia of Flange A	Bore of Slip-on B	Thickness of Flange C	Pitch circle Dia D	Dia of Bolt Holes E	No. of Bolts
6"	D	279	171	12.7	235	17.5	8
	E	279	171	17	235	22.2	8
	F	305	171	22	260	22.2	1
	H	305	171	29	260	22.2	1
8"	D	336	221.5	13	292	17.5	8
	E	336	221.5	19	292	22.2	8
	F	368	221.5	25	324	22.2	1
	H	368	221.5	32	324	22.2	1
10"	D	406	276.5	16	356	22.2	8
	E	406	276.5	25	356	22.2	1
	F	431	276.5	22	381	25.4	1
	H	431	276.5	35	381	25.4	1
12"	D	457	327	16	406	22.2	1
	E	457	327	29	406	25.4	1
	F	488	327	25	438	25.4	1
	H	488	327	38	438	25.4	1
14"	D	527	359	19	470	25.4	1
	E	527	359	32	470	25.4	1
	F	552	359	25	495	28.7	1
	H	552	359	41	495	28.7	1
16"	D	578	410.5	19	521	25.4	1
	E	578	410.5	32	521	25.4	1
	F	610	410.5	25	552	28.7	2
	H	610	410.5	44	552	32	2
18"	D	641	461.5	22	584	25.4	1
	E	641	461.5	35	584	25.4	1
	F	673	461.5	29	610	32	2
	H	673	461.5	48	610	32	2
20"	D	705	513	25	641	25.4	1
	E	705	513	28	641	25.4	1
	F	737	513	32	673	32	2
	H	737	513	51	673	32	2
24"	D	826	616	29	756	28.7	1
	E	826	616	38	756	32.3	1
	F	851	616	38	781	32	2
	H	851	616	57	781	35	2

